



Motori a corrente continua "AF" serie pesante
 Esecuzione IP23 protetta contro lo stitlicidio, autoventilata
DC "AF" (open with flange) motors - heavy line
 IP23 execution protected against tripping, self-ventilated

TIPO TYPE	PIAZZAMENTO POSITIONING					INGOMBRO MAX DIMENSIONS				ESTREMITA' ALBERO SHAFT END				J kg m ²	PESO WEIGHT kg
	L	M	N	O	P	D	E	F	G	d	e	v	z		
AF 80/ 7	215	180	4	9	14	250	320	270	290	24	50	27	8	0.012	30
AF 80/10	215	180	4	9	14	250	350	270	290	24	50	27	8	0.016	33
AF 80/14	215	180	4	9	14	250	390	270	290	24	50	27	8	0.023	38
AF 80/16	215	180	4	9	14	250	410	270	290	24	50	27	8	0.026	40
AF104/10	215	180	4	12	14	250	425	285	320	24	50	27	8	0.05	56
AF104/14	215	180	4	12	14	250	465	285	320	24	50	27	8	0.07	66
AF104/16	215	180	4	12	14	250	485	285	320	24	50	27	8	0.08	71
AF120/12	265	230	5	15	14	300	475	325	375	28	60	31	8	0.096	77
AF120/16	265	230	5	15	14	300	515	325	375	28	60	31	8	0.128	78



R.C.V. s.r.l.
 V. Cavour, 7 z.i.
 10070 Robassomero (TO) I
 Tel. 0039.0119241201
 Fax 0039.0119241176
 E-Mail: tecnico@rcv-srl.it