



Motori a corrente continua "AF..SC" serie pesante

Esecuzione IP23 protetta contro lo stillicidio, con ventilazione sussidiaria coassiale

DC "AF..SC" (open with flange) motors - heavy line

IP23 execution protected against tripping, with subsidiary coaxial ventilation

TIPO TYPE	PIAZZAMENTO POSITIONING					INGOMBRO MAX DIMENSIONS				ESTREMITA' ALBERO SHAFT END				J kg m ²	PESO WEIGHT kg
	L	M	N	O	P	D	E	F	G	d	e	v	z		
AF 80/ 7 SC	215	180	4	9	14	250	405	270	290	24	50	27	8	0.012	27
AF 80/10 SC	215	180	4	9	14	250	435	270	290	24	50	27	8	0.016	30
AF 80/14 SC	215	180	4	9	14	250	475	270	290	24	50	27	8	0.023	35
AF 80/16 SC	215	180	4	9	14	250	495	270	290	24	50	27	8	0.026	37
AF104/10 SC	215	180	4	12	14	250	490	285	320	24	50	27	8	0.050	65
AF104/14 SC	215	180	4	12	14	250	530	285	320	24	50	27	8	0.070	75
AF104/16 SC	215	180	4	12	14	250	550	285	320	24	50	27	8	0.080	75
AF120/12 SC	265	230	5	15	14	300	510	325	375	28	60	31	8	0.096	84
AF120/16 SC	265	230	5	15	14	300	550	325	375	28	60	31	8	0.128	95



R.C.V. s.r.l.
V. Cavour, 7 z.i.
10070 Robassomero (TO) I
Tel. 0039.0119241201
Fax 0039.0119241176
E-Mail: tecnico@rcv-srl.it