



Motori a corrente continua "APF" serie pesante
 Esecuzione IP23 protetta contro lo stilloccidio, autoventilata
DC "APF" (open with flange and feet) motors - heavy line
 IP23 execution protected against tripping, self-ventilated

TIPO TYPE	PIAZZAMENTO POSITIONING					FLANGIATURA FLANGE DIM.						INGOMBRO MAX DIMENSIONS				ESTREMITA' ALBERO SHAFT END				J kg m ²	PESO WEIGHT kg
	A	B	C	H	K	D	L	M	N	O	P	E	F	G	d	e	v	z			
APF 80/ 7	190	80	156	112	12	250	215	180	4	9	14	320	270	290	24	50	27	8	0.012	31	
APF 80/10	190	110	156	112	12	250	215	180	4	9	14	350	270	290	24	50	27	8	0.016	34	
APF 80/14	190	150	156	112	12	250	215	180	4	9	14	390	270	290	24	50	27	8	0.023	39	
APF 80/16	190	170	156	112	12	250	215	180	4	9	14	410	270	290	24	50	27	8	0.026	41	
APF104/10	202	130	176	132	12	250	215	180	4	12	14	425	300	320	24	50	27	8	0.050	58	
APF104/14	202	170	176	132	12	250	215	180	4	12	14	465	300	320	24	50	27	8	0.070	68	
APF104/16	202	190	176	132	12	250	215	180	4	12	14	485	300	320	24	50	27	8	0.080	73	
APF120/12	254	140	185	160	14	300	265	230	5	15	14	475	350	375	28	60	31	8	0.096	79	
APF120/16	254	180	185	160	14	300	265	230	5	15	14	515	350	375	28	60	31	8	0.128	90	



R.C.V. s.r.l.
 V. Cavour, 7 z.i.
 10070 Robassomero (TO) I
 Tel. 0039.0119241201
 Fax 0039.0119241176
 E-Mail: tecnico@rcv-srl.it