



Motori a corrente continua "AP" serie pesante
 Esecuzione IP23 protetta contro lo stitlicidio, autoventilata
DC "AP" (open with feet) motors - heavy line
 IP23 execution protected against tripping, self-ventilated

TIPO TYPE	PIAZZAMENTO POSITIONING					INGOMBRO MAX DIMENSIONS			ESTREMITA' ALBERO SHAFT END				PULEGGIA PULLEY		J kg m ²	PESO WEIGHT kg
	A	B	C	H	K	E	F	G	d	e	v	z	∅ min.	L max		
AP 80/7	190	80	108	112	12	302	245	250	24	50	27	8	60	50	0.012	24
AP 80/10	190	110	108	112	12	332	245	250	24	50	27	8	60	50	0.016	27
AP 80/14	190	150	108	112	12	372	245	250	24	50	27	8	60	50	0.023	32
AP 80/16	190	170	108	112	12	392	245	250	24	50	27	8	60	50	0.026	34
AP104/10	202	130	127	132	12	392	300	320	24	50	27	8	90	50	0.050	50
AP104/14	202	170	127	132	12	432	300	320	24	50	27	8	90	50	0.070	60
AP104/16	202	190	127	132	12	452	300	320	24	50	27	8	90	50	0.080	65
AP120/12	254	140	132	160	14	415	350	375	28	60	31	8	140	60	0.096	69
AP120/16	254	180	132	160	14	455	350	375	28	60	31	8	140	60	0.128	80



R.C.V. s.r.l.
 V. Cavour, 7 z.i.
 10070 Robassomero (TO) I
 Tel. 0039.0119241201
 Fax 0039.0119241176
 E-Mail: tecnico@rcv-srl.it